



Professional integrated solar street light manufacture
专注铝材一体化太阳能路灯——专注道路照明

Professional integrated solar street light manufacture
专注铝材一体化太阳能路灯——专注道路照明



专注一体化太阳能路灯研发、生产10年!



BKD-602-2



BKD-602-3



BKD-602-4

Technical Data 技术参数

Model/型号	BKD-602-2	BKD-602-3	BKD-602-4
Power/功率	200W	300W	400W
Solar panel/太阳能板	6V/50W	6V/70W	18V/90W
Battery/电池容量	3.2V/36Ah-LiFePO4	3.2V/50Ah-LiFePO4	12.8V/28Ah-LiFePO4
Leds/灯珠数量	SMD3030	SMD3030	SMD3030
Material/材质	Aluminum alloy	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control	Segmented Time control
LED Brand/芯片	Bridgelux-USA	Bridgelux-USA	Bridgelux-USA
LifeTime/寿命	>50000hrs	>50000hrs	>50000hrs
Discharge Time/放电时间	5-7 rainy days	5-7 rainy days	5-7 rainy days
Charge Time/充电时间	9-12hrs	9-12hrs	9-12hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	4-5M	5-7M	6-9M
Product Size/产品尺寸	685*362*45MM	1000*362*45MM	1295*362*45MM
Packing Size/包装尺寸	75*41.5*10cm 37*16*10cm	106*41.5*10cm 50*16*10cm	133.5*41.5*10cm 70*16*10cm
Net Weight/净重	7.32kg	10.38kg	14.8kg
Gross Weight/毛重	8.26kg	11.33kg	15.7kg
20GP/装柜数量	780PCS	554PCS	436PCS
40GP/装柜数量	1561PCS	1109PCS	872PCS
40'HQ/装柜数量	1895 PCS	1346 PCS	1059PCS



BKD-502-2




BKD-502-3



BKD-502-4

Technical Data 技术参数

Model/型号	BKD-502-2	BKD-502-3	BKD-502-4
Power/功率	200W	300W	400W
Solar panel/太阳能板	6V/35W	6V/50W	6V/70W
Battery/电池容量	3.2V/20Ah-LiFePO4	3.2V/30Ah-LiFePO4	3.2V40Ah-LiFePO4
Leds/灯珠数量	SMD3030	SMD3030	SMD3030
Material/材质	Aluminum alloy	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control	Segmented Time control
LED Brand/芯片	3030-1/W	3030-1/W	3030-1/W
LifeTime/寿命	>50000hrs	>50000hrs	>50000hrs
Discharge Time/放电时间	3-5 rainy days	3-5 rainy days	3-5 rainy days
Charge Time/充电时间	6-9hrs	6-9hrs	9-12hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	4-5M	5-6M	5-8M
Product Size/产品尺寸	530*362*32MM	685*362*32MM	1000*362*32MM
Packing Size/包装尺寸	58*40.5*8.5cm 32*19*14cm	73.5*40.5*8.5cm 37*16*10cm	104.5*40.5*8.5cm 50*16*10cm
Net Weight/净重	5.6kg	6.3kg	8.5kg
Gross Weight/毛重	6.5kg	7.2kg	9.5kg
20GP/装柜数量	1278PCS	941PCS	665PCS
40GP/装柜数量	2556PCS	1882PCS	1331PCS
40'HQ/装柜数量	3103 PCS	2286PCS	1616PCS



Technical Data 技术参数

Model/型号	BK-202-300
Power/功率	300W
Solar panel/太阳能板	6V/35W
Battery/电池容量	3.2V/36Ah-LiFePO4
Leds/灯珠数量	52X6
Material/材质	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control
LED Brand/芯片	LED 灯珠
LifeTime/寿命	>50000hrs
Discharge Time/放电时间	3-5 rainy days
Charge Time/充电时间	6-9hrs
Working Temperature/工作温度	-20°C~+60°C
Install Height/安装高度	3-6M
Product Size/产品尺寸	Ø 520MM.Mouted Diam 76MM Ø 520MM,套筒内径76MM
Packing Size/包装尺寸	56*56*30cm
Net Weight/净重	7.0kg
Gross Weight/毛重	7.4kg
20GP/装柜数量	283PCS
40GP/装柜数量	565PCS
40'HQ/装柜数量	687PCS


Professional integrated solar street light manufacture

专注铝材一体化太阳能路灯——专注道路照明



Professional integrated solar street light manufacture

专注铝材一体化太阳能路灯——专注道路照明



Technical Data 技术参数

Model/型号	BK-202-400
Power/功率	400W
Solar panel/太阳能板	6V/70W
Battery/电池容量	3.2V/50Ah-LifePo4
Leds/灯珠数量	52X8
Material/材质	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control
LED Brand/芯片	LED 灯珠
LifeTime/寿命	>50000hrs
Discharge Time/放电时间	3-5 rainy days
Charge Time/充电时间	6-9hrs
Working Temperature/工作温度	-20℃~+60℃
Install Height/安装高度	3-6M
Product Size/产品尺寸	Ø 760MM.Mouted Diam 76MM Ø 760MM,套筒内径76MM
Packing Size/包装尺寸	78 × 78 × 18.5cm
Net Weight/净重	9.0kg
Gross Weight/毛重	10kg
20GP/装柜数量	236PCS
40GP/装柜数量	473PCS
40'HQ/装柜数量	574PCS



BKD-602-3-J



BKD-602-4-J

Technical Data 技术参数

Model/型号	BKD-602-3-J	BKD-602-4-J
Power/功率	300W	400W
Solar panel/太阳能板	6V/70W	18V/90W
Battery/电池容量	3.2V/62Ah-LifePo4	12.8V/30Ah-LifePo4
Leds/灯珠数量	SMD3030	SMD3030
Material/材质	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control
LED Brand/芯片	3030-1/W	3030-1/W
LifeTime/寿命	>50000hrs	>50000hrs
Discharge Time/放电时间	3-5 rainy days	3-5 rainy days
Charge Time/充电时间	6-9hrs	6-9hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	6-9M	6-10M
Product Size/产品尺寸	1000*362*45MM	1295*362*45MM
Packing Size/包装尺寸	106*41.5*18cm	138.5*41.5*18cm
Net Weight/净重	10.6kg	16.1kg
Gross Weight/毛重	11.3kg	17.1kg
20GP/装柜数量	336PCS	257PCS
40GP/装柜数量	672PCS	514PCS
40'HQ/装柜数量	816 PCS	624PCS



Technical Data 技术参数

Model/型号	BKD-602H-150	BKD-602H-300	BKD-602H-450
Power/功率	150W	300W	450W
Solar panel/太阳能板	6V/35W	6V/50W	6V/70W
Battery/电池容量	3.2V/24Ah-LifePo4	3.2V/36Ah-LifePo4	3.2V/50Ah-LifePo4
Leds/灯珠数量	SMD3030	SMD3030	SMD3030
Material/材质	Aluminum alloy	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control	Segmented Time control
LED Brand/芯片	3030-1/W	3030-1/W	3030-1/W
LifeTime/寿命	>50000hrs	>50000hrs	>50000hrs
Discharge Time/放电时间	5-7 rainy days	5-7 rainy days	5-7 rainy days
Charge Time/充电时间	9-12hrs	9-12hrs	9-12hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	5-6M	5-8M	6-9M
Product Size/产品尺寸	530*362*45MM	685*362*45MM	1000*362*45MM
Packing Size/包装尺寸	66.5*41.5*10cm	82*41.5*10cm	114*41.5*10cm
Net Weight/净重	5.83kg	7.4kg	10.5kg
Gross Weight/毛重	6.6kg	8.4kg	11.5kg
20GP/装柜数量	964PCS	782PCS	562PCS
40GP/装柜数量	1928PCS	1563PCS	1124PCS
40'HQ/装柜数量	2341 PCS	1898PCS	1365PCS



Technical Data 技术参数

Model/型号	BKD-502H-150	BKD-502H-300	BKD-502H-450
Power/功率	150W	300W	450W
Solar panel/太阳能板	6V/35W	6V/50W	6V/70W
Battery/电池容量	3.2V/20Ah-LifePo4	3.2V/30Ah-LifePo4	3.2V/40Ah-LifePo4
Leds/灯珠数量	SMD3030	SMD3030	SMD3030
Material/材质	Aluminum alloy	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control	Segmented Time control
LED Brand/芯片	3030-1/W	3030-1/W	3030-1/W
LifeTime/寿命	>50000hrs	>50000hrs	>50000hrs
Discharge Time/放电时间	3-5 rainy days	3-5 rainy days	3-5 rainy days
Charge Time/充电时间	9-12hrs	9-12hrs	9-12hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	3-5M	4-6M	5-7M
Product Size/产品尺寸	528*351*38MM	683*351*38MM	996*351*38MM
Packing Size/包装尺寸	66*40*8.5cm	81*40*8.5cm	113*40*8.5cm
Net Weight/净重	5.5kg	6.23kg	8.2kg
Gross Weight/毛重	6.5kg	7.1kg	9.2kg
20GP/装柜数量	1185PCS	960PCS	692PCS
40GP/装柜数量	2371PCS	1920PCS	1385PCS
40'HQ/装柜数量	2879 PCS	2331PCS	1681PCS

Professional integrated solar street light manufacture

专注铝材一体化太阳能路灯——专注道路照明



LIGHTING 365 DAYS

365天亮灯
户外防雨

OUTDOOR WATERPROOF
LIGHTING UP LIFE

Professional integrated solar street light manufacture

专注铝材一体化太阳能路灯——专注道路照明



BKD-503-2



BKD-503-3



BKD-503-4

Technical Data 技术参数

Model/型号	BKD-503-2	BKD-503-3	BKD-503-4
Power/功率	80W	120W	160W
Solar panel/太阳能板	6V/18W	6V/24W	6V/30W
Battery/电池容量	3.2V/12Ah-LifePo4	3.2V/20Ah-LifePo4	3.2V/24Ah-LifePo4
Leds/灯珠数量	SMD3030	SMD3030	SMD3030
Material/材质	Aluminum alloy	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control	Segmented Time control
LED Brand/芯片	3030-1/W	3030-1/W	3030-1/W
LifeTime/寿命	>50000hrs	>50000hrs	>50000hrs
Discharge Time/放电时间	3-5 rainy days	3-5 rainy days	3-5 rainy days
Charge Time/充电时间	9-12hrs	9-12hrs	9-12hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	4-5M	5-6M	5-6M
Product Size/产品尺寸	486*192*88MM	570*192*88MM	775*192*88MM
Packing Size/包装尺寸	61.5*24*8.5cm	69.5*24*8.5cm	90*24*8.5cm
Net Weight/净重	1.85kg	2.35kg	3.35kg
Gross Weight/毛重	2.27kg	2.79kg	3.9kg
20GP/装柜数量	2120PCS	1876PCS	1449PCS
40GP/装柜数量	4240PCS	3752PCS	2898PCS
40'HQ/装柜数量	5149PCS	4556PCS	3519PCS



365天亮灯
户外防雨

LIGHTING 365 DAYS
OUTDOOR WATERPROOF
LIGHTING UP LIFE



BKD-503-1



BKD-503-2

Technical Data 技术参数

Model/型号	BKD-503-1	BKD-503-2
Power/功率	100W	200W
Solar panel/太阳能板	6V/12W	6V/18W
Battery/电池容量	3.2V/8Ah-LiFePO4	3.2V/12Ah-LiFePO4
Leds/灯珠数量	SMD2835	SMD2835
Material/材质	Aluminum alloy	Aluminum alloy
Working Mode/亮灯方式	Segmented Time control	Segmented Time control
LED Brand/芯片	3030-1/W	3030-1/W
LifeTime/寿命	>50000hrs	>50000hrs
Discharge Time/放电时间	24-48hrs	24-48hrs
Charge Time/充电时间	6-9hrs	6-9hrs
Working Temperature/工作温度	-20℃~+60℃	-20℃~+60℃
Install Height/安装高度	3M	3M
Product Size/产品尺寸	372*192*88mm	486*192*88mm
Packing Size/包装尺寸	49.5*24*8.5cm	61.5*24*8.5cm
Net Weight/净重	1.56kg	1.85kg
Gross Weight/毛重	1.85kg	2.27kg
20GP/装柜数量	2634PCS	2120PCS
40GP/装柜数量	5268PCS	4240PCS
40'HQ/装柜数量	6397 PCS	5149PCS